→ PTO-CENTRAL-OFFI Ø1003

04/27/2005 15:35 FAX 3142382401

Appl. No. 10/626,136

Amdt. dated April 27, 2005

Reply to Office action of March 23, 2005

This listing of claims will replace all prior versions, and listings, of claims in

the application:

Listing of Claims:

A can opener for a pull top-type can, the (Currently Amended) 1.

opener comprising:

a body comprising a forward surface, a rear surface, and a bottom surface,

at least said bottom surface being curved to define a generally U-shaped heel;

a tab engaging lip having a flat surface extending rearwardly from an upper,

forward end of said heel; said lip flat surface forming an acute intersection with

said heel and having a length less then the diameter of a ring of a pull-top can

opening tab;

a starting notch at an rear end of said tab engaging lip flat surface opposite

said intersection between said flat surface and said heel, said starting notch

having a forward surface and a bottom surface; said lip flat surface and said notch

bottom surface intersecting with said notch forward surface at opposite ends of

said notch forward surface; said starting notch forward surface defining an angle

with said lip flat surface to form an abrupt transition between said flat surface and

said notch; and

a finishing notch at said front surface; said-starting notch having a bottom

surface below said lip-surface; said starting and finishing notches being sized and

Page 2

April 27, 2005 HAWK 8693US - Amendment B.doc

Appl. No. 10/626,136 Amdt. dated April 27, 2005

Reply to Office action of March 23, 2005

shaped to receive a ring of an opening tab of a can to be opened and having a ferward-surface against which said tab ring can engage; said finishing notch being spaced above said starting notch.

2. (Original) The can opener of claim 1 including a handle, said body being formed at one end of said handle.

3. (Previously Presented) The can opener of claim 1 wherein said heel has a first portion defining a first radius extending from said flat surface and a second portion defining a second radius, said second radius continuing from said first radius; said first radius being greater than said second radius.

4. (Currently Amended) The can opener of claim 1 including a port opening into said starting notch from said front surface; said <u>flat</u> surface defining a lower surface of said port.

5. (cancel)

6. (Original) The can opener of claim 4 wherein said port is a first port, said opener including a second port spaced above said first port; said second port opening into said finishing notch.

7. (Previously Presented) The can opener of claim 6 wherein said body includes a retaining portion which extends over said opening; said retaining portion being adapted to maintain a can lid on said opener upon removal of the can lid from its can.

Page 3

April 27, 2005 HAWK 8693US - Amendment Budge Appl. No. 10/626,136 Amdt. dated April 27, 2005 Reply to Office action of March 23, 2005

- 8. (Withdrawn) The can opener of claim 7 wherein said second port defines a spiral path; said second port surfaces defining said retaining portion.
- 9. (Withdrawn) The can opener of claim 4 including a channel extending from said starting notch to said finishing notch; said can opener having only a single port.
- 10. (Withdrawn) The can opener of claim 9 wherein said finishing notch is on a forward edge of said channel.
- 11. (Withdrawn) The can opener of claim 9 wherein said finishing notch is on a rear edge of said channel.
- 12. (Withdrawn) The can opener of claim 9 including a rebound slot extending generally rearwardly from said channel.
- 13. (Withdrawn) The can opener of claim 1 including an arm pivotally mounted to said body above said finishing notch; said arm having a downwardly extending finger; said arm being movable between a first position in which said finger engages a front edge of said notch to close said notch and a second position in which said finger is spaced above said notch front edge to open said notch.
- 14. (Withdrawn) The can opener of claim 13 wherein said arm is spring biased to its first position.

Page 4

April 27, 2005 HAWK 8693US - Amendment Budge Appl. No. 10/626,136 Amdt. dated April 27, 2005 Reply to Office action of March 23, 2005

15. (Currently Amended) A can opener for a pull top-type can, the opener comprising a body comprising:

a forward surface, a rear surface, and a bottom surface, at least said bottom surface being curved to define a generally U-shaped heel;

a tab engaging lip having a surface extending rearwardly from an upper, forward end of said heel; said surface forming an acute intersection with said heel;

a starting notch at a rear end of said tab engaging lip surface opposite said intersection between said lip surface and said heel; said starting notch having a forward surface and a bottom surface below said lip surface and said starting notch being sized and shaped to receive a ring of an opening tab of a can to be opened; said lip surface and said notch bottom surface intersecting with said notch forward surface at opposite ends of said notch forward surface; said starting notch forward surface defining an angle with said lip surface to form an abrupt transition between said surface and said notch;

a finishing notch at said front surface; said finishing notch being spaced above said starting notch; and

a retainer proximate said finishing notch; said retainer being adapted to maintain a can lid on said opener upon removal of the can lid from its can;

the curvature of the generally U-shaped heel being sized such that when a can opening tab is received in the starting notch, pivoting of the can opener about

Page 5

April 27, 2005 HAWK 8693US - Ameridment Budge 04/27/2005 15:37 FAX 3142382401

the can.

→ PTO-CENTRAL-OFFI 2007

Appl. No. 10/626,136 Amdt. dated April 27, 2005

Reply to Office action of March 23, 2005

the heel will pivot the tab sufficiently to cause the tab to break the seal of the can lid and the rounded heel is sized such that when the opening tab is received in the finishing notch, pivoting of the can opener about the heel will remove the lid from

16. (Original) The can opener of claim 15 including a first port in communication with said starting notch and a second port in communication with said finishing notch; said first port extending from a forward surface of said body to said starting notch; said second port extending from one of said forward surface or an upper surface of said body.

17. (Withdrawn) The can opener of claim 15 including a port extending from said forward edge of said opener body to said starting notch and a channel extending from said starting notch to said finishing notch.

18. (Original) The can opener of claim 15 wherein said retainer is defined by a lip; said lip defining at least a part of a channel extending from said forward edge of said opener body to said finishing notch.

19. (Previously Presented) The can opener of claim 15 wherein said retainer comprises a pathway extending from said finishing notch toward a surface of said body to define a port in said body surface; said port being above said finishing notch.

Page 6

April 27, 2005 HAWK 8693US - Amendment 8.doc Appl. No. 10/626,136 Amdt. dated April 27, 2005 Reply to Office action of March 23, 2005

- 20. (Previously Presented) The can opener of claim 19 wherein said pathway is generally J-shaped.
- 21. (Previously Presented) The can opener of claim 20 wherein said J-shaped pathway is a generally inverted J-shaped pathway.
- 22. (Previously Presented) The can opener of claim 1 wherein the bottom of the U-shaped heel forms a fulcrum about which the body rotates on top of the lid (1) to raise the a can opening tab when the tab is engaged in the starting notch and (2) to pry the can lid off the can when the tab is engaged in the finishing notch.